


 MP 5000D


 TTI DESCRIPTION

- Mounted mud pump & welding machine
- Mounted Hyd. power pack
- Pull up Max. 50 ton with winch
- Mounted Hyd. Drifter as option
- Auto change system or crane for drill pipe as option



MP 5000D


 TTI SPECIFICATION

6.8M (L) x 1.9M (W) x 2.5M (H) x 7.5ton(W)						
Engine	Model	Hyundai D6BT-G1	Feed System	Feed Cylinder	150 mm x 110 mm x 1850 mm	
	Rated Power	180HP/1800rpm		Head Travel	3.7 M	
	Fuel Capacity	150L		Pull Up	30 ton	
	Cooling System	Water Cooling		Pull Down	14 ton	
Rotation	Reducing	Super Gear-4.35 to 1	Mud Pump	JDMP 200-80H (200L/min)		
	Performance	Two Motor (STD)	Under-carriage	Type	Sola 055	
	Max. RPM	1st		0 ~ 100	Speed	2.5 km/h
		2nd		0 ~ 50	Ground Pressure	0.6 kg/cm ²
	Max. Torque	1st		600 kg.m	3-Web Track Shoe	300 mm
		2nd	1200 kg.m	Ground Clearance	300 mm	
OPTION Hydraulic Drifter : JDMD800 Mud Pump : JDMP400 (400L/min) Winch : 20 ton Crane or Auto Rod Changer						