


MP 5000CD
TIT SPECIFICATION

6.0M (L) x 2.4M (W) x 1.5M (H) x 5.5ton(W)			
Engine	Model	Hyundai D4AK-G	
	Max. Power	74HP/1800rpm	
Top Head Rotation	R.P.M	1st	0 ~ 100
		2nd	0 ~ 50
	Torque	1st	200 kg.m
		2nd	400 kg.m
Feed System	Head Travel	3.7 M	
	Pullup Capacity	8 ton	
	Pulldown Capacity	3 ton	
Drill pipe	Max. Length	3 M	
	Max. Diameter	101 mm (4")	
Winch	Option		
Welder	Option		
Hydraulic Clamp	φ 43 ~ φ 165		
Hydraulic Drifter	Option		
Dust Collector	Option		
Drilling Capacity : Tricon & DTH	3" ~ 6"		
OPTION	Hydraulic Drifter : JDMD700, JDMD800 Mud Pump : 200LPM Compressor : 400CFM/ 200PSI Winch & Dust Collector & Welder Water Injection Pump (40LPM/ 35 bar)		

TIT CHARACTER

1. This model is for blast hold
2. Can be installed compressor (400CFM/ 200PSI) as option
3. The compressor can drill 3" ~ 6" hammer for blast hole
4. This model can be installed Hyd. drifter as option
5. Integrated dry dust collector
6. Can drill vertical, angle & horizontal drilling



MP 5000CD