


OVERBURDEN

TT ADVANTAGES

- Down-hole casing keeps formation from collapsing making well installation easier.
- No drilling fluids required.
- System works with Hollow Stem Auger rigs resulting in cost savings compared to larger air rotary rigs.
- Reduced drilling time vs. conventional mud rotary systems.
- Temporary isolation from upper water bearing formations.



Extended Position



Retracted Position

Model	Size	Type	Bit-Diameter (mm)		Shoulder Dia. (mm)	Over Cut (mm)	Casing Size (mm)			Suitable Hammer Type
			Extended	Retracted			I.D	O.D.	Wall	
NEX-6B	140	2WINGS	190.5	141	150.8	11.1	155.2	168.2	6.5	IR 340, SD 4
NEX-7B	165	2WINGS	222.2	167	176.2	14.3	178.4	193.6	7.6	IR 360, SD 6
NEX-8B	190	3WINGS	254	189	201.6	17.5	203.8	219	7.6	IR 360, SD 6
NEX-9B	215	3WINGS	279.4	219	235	12.7	241.2	254	6.4	IR 380, SD 8
NEX-10B	240	3WINGS	311.1	235	251.2	19	254.6	273	9.2	IR 380, SD 8
NEX-12B	280	3WINGS	335	281.5	299	8.3	305.7	318.5	6.4	IR 310, SD 10
NEX-14B	320	3WINGS	373	320	333	8.7	336.6	355.6	9.5	IR 112, SD 12
NEX-16B	365	3WINGS	425	363	384	9.3	387.4	406.4	9.5	IR 112, SD 12
NEX-18B	410	3WINGS	478	410	432	10.4	435	457.2	11.1	IR 112, SD 12
NEX-20B	460	3WINGS	530	455	480	11	482.6	508	12.7	SD 18, N 180
NEX-22B	510	4WINGS	581	506	520	11.1	533.4	558.8	12.7	SD 18, N 180
NEX-24B	560	4WINGS	632	557	581	11.2	584.2	609.6	12.7	SD 18, N 180
NEX-26B	610	4WINGS	685	603	631	12.3	635	660.4	12.7	SD 24, N 240
NEX-28B	660	4WINGS	737	652	682	12.9	685.8	711.2	12.7	SD 24, N 240
NEX-30B	710	4WINGS	784	706	733	11	736.6	762	12.7	SD 24, N 240
NEX-32B	750	4WINGS	850	748	782	18.6	787.4	812.8	12.7	SD 24, N 240
NEX-34B	810	4WINGS	886	808	834	11.2	838.2	863.6	12.7	N 300